



Hammock Seat Cover Care & Use Guide

Thank you for purchasing the Solvit Products Hammock Style Seat Cover. This cover is designed to fit all automotive rear seat areas with headrests.

INSTALLATION: The cover is held in place by adjustable straps which go around the two rear headrests and the two front headrests. The straps that go over the front headrests are those next to the storage pockets. Lay the cover in place on the rear seat, loop the straps over the headrests and adjust the strap length for the best fit.

Next, locate the two Sta-put™ devices on the underside of the seat cover. These consist of a short piece of plastic tubing attached to the cover by a short strap. Push the tube into the space where the seat back meets the seat bottom cushion. The Sta-puts can be removed with a strong tug, but will hold firmly enough to keep the cover in place under normal use.



Side vents: The cover includes two side vents which can be opened or closed by means of hook and loop tape. For narrower vehicles, the fit will be improved by leaving the vents open. Experiment to find the best fit for your vehicle.

Seat belt slits: The cover also includes two slits which allow seat belt buckles to pass through. These slits are oversized to fit all vehicle configurations. For your pet's comfort, we suggest stowing the buckles under the cover when not in use.



Cleaning: Promptly wipe up any foreign matter or standing liquid with a damp cloth or sponge. Machine wash the cover in a commercial size front loading washing machine. Use cold water with a mild detergent. Line dry.

CAUTION: Always make sure the vehicle seat is dry before installing the seat cover.

Warranty: The Hammock Style Seat Cover is warranted to be free from defects in materials or workmanship for a period of one (1) year from date of purchase. A copy of the original sales receipt is required for warranty issues.