

MATERIAL SAFETY DATA SHEET

WEAVER LEATHER LLC  
PO BOX 68  
MT. HOPE OHIO 44660

PRODUCT NAME: PRO TOUCH WHITE POWDER TOUCH-UP

EMERGENCY TELEPHONE: 800-255-3924  
INFORMATION TELEPHONE: 330-674-7548

REVISION DATE: 9-01-06  
PRODUCT NUMBER: 69-2106

**SECTION I. IDENTIFICATION**

CHEMICAL NAME: HEXANE  
FORMULA: 69-2106  
SYNONYMS: POWDER WHITE TOUCH UP  
DOT HAZARD CLASSIFICATION: ORM-D  
DOT SHIPPING NAME: CONSUMER COMMODITY  
**INTERNATIONAL SHIPMENTS:**  
AEROSOLS, FLAMMABLE  
CLASS 2.1  
UN 1950  
CHEMICAL ABSTRACT REGISTRY NUMBER: N/A, MIXTURE  
IDENTIFICATION NUMBER: NONE  
H.M.I.S. RATING: 2,4,0,B

**SECTION II. PHYSICAL DATA**

BOILING POINT: 103-104 DEGREES F.  
FREEZING POINT: <-40 DEGREES F.  
SPECIFIC GRAVITY: (H2O=1): 0.644  
WEIGHT PER GALLON @ 60 F.: 5.378  
VAPOR PRESSURE OF CONCENTRATE @ 70 F. (MM HG): 137  
VAPOR DENSITY (AIR= 1): > 1  
SOLUBILITY IN WATER, % BY WEIGHT: NIL  
EVAPORATION RATE (MINUTES): FAST  
APPEARANCE AND ODOR: BLACK

**SECTION III. HAZARDOUS INGREDIENTS**

MATERIAL:	APPROX. WT.%	CAS NUMBER:	PEL(OSHA)
PROPYLENE GLYCOL METYL-ETHER ACETATE	6.5	108-65-6	N/A
TITANIUM DIOXIDE	10	13463-67-7	10 mg/M3
ZINC STEARATE	6-8	557-05-1	N/A
HEXANE	55-65	110-54-3	50 PPM
N-BUTANE	5-10	106-97-8	1000
ISOBUTANE	4-8	75-28-5	1000
PROPANE	10-20	74-98-6	1000

\*CONTAINS NO OZONE DEPLETING CHEMICALS\*  
ALL COMPONENTS OF THIS PRODUCT ARE LISTED ON THE TSCA DIRECTORY

**SECTION IV. FIRE AND EXPLOSION HAZARD DATA**

FLAMMABLE LIMITS IN AIR: LEL: 1.2 UEL: 7.5 (VOLUME %)  
EXTREMELY FLAMMABLE: AEROSOL FLAME PROJECTION TEST GREATER THAN 18 INCHES  
SPECIAL FIRE FIGHTING PROCEDURES: FIRE FIGHTERS SHOULD BE EQUIPPED WITH SELF-CONTAINED BREATHING APPARATUS.  
UNUSUAL FIRE & EXPLOSION HAZARDS: AEROSOLS MAY RUPTURE VIOLENTLY WHEN HEATED TO TEMPERATURES OVER 120' F. VERY FLAMMABLE. AVOID OPEN FLAME. VAPORS MAY BECOME EXPLOSIVE WITH ACCUMULATION.

---

**SECTION V. REACTIVITY DATA**

---

STABILITY: STABLE  
INCOMPATIBILITY (MATERIALS TO AVOID): NONE KNOWN  
HAZARDOUS COMBUSTION BY-PRODUCTS: SEE SECTION IV  
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR  
CONDITIONS TO AVOID: TEMP. ABOVE 120' F. – DIRECT SUNLIGHT

---

**SECTION VI. HEALTH HAZARD DATA**

---

THRESHOLD LIMIT VALUE: 50 PPM

• **EFFECTS OF OVEREXPOSURE \***

INGESTION (SWALLOWING): N/A  
INHALATION: HEADACHES, NAUSEA, DIZZINES, DECREASED BLOOD PRESSURE  
SKIN CONTACT: DEFATTING OF SKIN  
EYE CONTACT: TEMPORARY IRRITATION

• **EMERGENCY AND FIRST AID PROCEDURES \***

SKIN: WASH WITH SOAP AND WATER, APPLY HAND CREAM  
INHALATION: REMOVE TO FRESH-AIR LOCATION AWAY FROM EXPOSURE  
EYES: RINSE WITH PLENTY COOL CLEAN WATER UNTIL IRRITATION SUBSIDES

---

**SECTION VII. SPILL OR LEAK PROCEDURES**

---

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: REMOVE LEAKING CONTAINER TO OUTSIDE DISPOSAL SITE.  
WASTE DISPOSAL METHOD: EMPTY FULLY, INCLUDING GAS PRESSURE. DO NOT PUNCTURE OR INCINERATE. CAN MAY BE RECYCLED OR ALTERNATIVELY REMOVED TO A SANITARY LANDFILL – CHECK APPLICABLE REGULATIONS.

---

**SECTION VIII. SPECIAL PROTECTION INFORMATION**

---

RESPIRATORY PROTECTION (SPECIFY TYPE): NOT NEEDED WITH ADEQUATE VENTILATION  
VENTILATION: ADEQUATE VENTILATION RECOMMENDED  
PROTECTIVE GLOVES: NOT REQUIRED BUT RECOMMENDED  
EYE PROTECTION: PROPER EYE CARE IS NEEDED IN ALL INDUSTRIAL OPERATIONS  
OTHER PROTECTIVE EQUIPMENT: AS REQUIRED BY YOUR COMPANY.

---

**SECTION IX. SPECIAL PRECAUTIONS**

---

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE INDOORS AWAY FROM HEAT SOURCES OR DIRECT SUNLIGHT-DO NOT PUNCTURE OR INCINERATE-DO NOT DROP!!  
OTHER PRECAUTIONS: EXTREMELY FLAMMABLE. TAKE CARE TO AVOID SOURCES OF IGNITION. AVOID OVER-SPRAYING ONTO FLOORS OR SLIPPERY SURFACE MAY RESULT.

THIS DATA IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EXPRESS OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE AND DETERMINE WHETHER THEY ARE APPROPRIATE. THE INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET IS BELIEVED TO BE CORRECT AS OF THIS DATE. THE REGULATIONS PROMULGATED BY OSHA FOR HAZARD COMMUNICATION, 29 CFR 1910.1200, AS WELL AS SEVERAL STATE AND LOCAL LAWS AND REGULATIONS, HAVE BEEN CONSULTED IN PREPARING THIS M.S.D.S.

---