

MATERIAL SAFETY DATA SHEET
WEAVER LEATHER LLC
PO BOX 68
MT. HOPE OHIO 44660
PRODUCT NAME: PRO GLOSS FINISHING SPRAY

EMERGENCY TELEPHONE# 800-255-3924
INFORMATION TELEPHONE#330-674-7548

REVISION DATE: 9-01-06
PRODUCT NUMBER:69-2200

SECTION I. IDENTIFICATION

CHEMICAL NAME: ALIPHATIC HYDROCARBON
CHEMICAL FAMILY: SEE ABOVE
FORMULA: 69-2200
SYNONYMS: HI-GLOSS
DOT HAZARD CLASSIFICATION: CONSUMER COMMODITY, ORM-D
INTERNATIONAL SHIPMENTS:
AEROSOLS, FLAMMABLE
CLASS 2.1
UN 1950
CHEMICAL ABSTRACT REGISTRY NUMBER: N/A -MIXTURE
IDENTIFICATION NUMBER:
PACKING GROUP:
H.M.I.S. RATING: 2,3,0,G

SECTION II. PHYSICAL DATA

BOILING POINT: RANGE 103-232 DEGREES F.
FREEZING POINT: <-40 DEGREES F.
SPECIFIC GRAVITY [H20=1]: 1.1534
WEIGHT PER GALLON @ 60 F.: 9.625
VAPOR PRESSURE @70 f. {MM HG}: 350
VAPOR DENSITY [AIR=1]: >1
SOLUBILITY IN WATER, %BY WT.: NIL
PERCENT VOLATILE BY VOLUME: 94
EVAPORATION RATE [MINUTES]: 3
APPEARANCE AND ODOR: WHITE

SECTION III. HAZARDOUS INGREDIENTS

| MATERIAL: | APPROX. VOLUME%: | CAS NUMBER: | TLV[UNITS]: |
|-----------------------|------------------|-------------|-------------|
| ALIPHATIC HYDROCARBON | 29 | 64742-48-9* | 300 PPM |
| ALIPHATIC HYDROCARBON | 41 | 8042-47-59 | N/A |
| N-BUTANE | 5-10 | 106-97-8 | 1000 |
| ISOBUTANE | 4-8 | 75-28-5 | 1000 |
| PROPANE | 10-20 | 74-98-6 | 1000 |

SECTION IV. FIRE AND EXPLOSION HAZARD DATA

FLAMMABLE LIMITS IN AIR: LEL: N/A UEL: N/A (VOLUME %)
FLAMMABLE AEROSOL PER THE AEROSOL FLAME PROJECTION TEST
FLASH POINT: NONE
EXTINGUISHING MEDIA: NONE
SPECIAL FIRE FIGHTING PROCEDURES: NONE
UNUSUAL FIRE & EXPLOSION HAZARDS: AEROSOLS MAY EXPLODE

SECTION V. REACTIVITY DATA

STABILITY: STABLE

INCOMPATIBILITY (MATERIALS TO AVOID): ALKALINE EARTH METALS, OXIDIZERS, BASES, AND REACTIVE METALS. INCOMPATIBLE WITH NATURAL RUBBER

HAZARDOUS COMBUSTION BY-PRODUCTS: CO, CO₂ AND HBr

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

CONDITIONS TO AVOID: OPEN FLAMES AND HIGH TEMPERATURES

SECTION VI. HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: 300 PPM

EFFECTS OF OVEREXPOSURE

INGESTION [SWALLOWING]: GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING

INHALATION: EXCESSIVE INHALATION CAN CAUSE DIZZINESS, WEAKNESS, HEADACHE, OR POSSIBLE UNCONSCIOUSNESS

SKIN CONTACT: PROLONGED CONTACT CAUSES MODERATE IRRITATION, DE-FATTING

EYE CONTACT: IRRITATION, REDNESS, TEARING, BLURRED VISION

EMERGENCY AND FIRST AID PROCEDURES

INGESTION: DO NOT INDUCE VOMITING, CALL PHYSICIAN

SKIN: WASH WITH NAPHTHA, THEN SOAP AND WATER - APPLY HAND CREAM

INHALATION: REMOVER TO FRESH AIR, ADMINISTER OXYGEN IF NECESSARY.

EYES: FLUSH WITH LARGE AMOUNTS OF COOL CLEAN WATER UNTIL IRRITATION SUBSIDES.

SECTION VII. SILL OR LEAK PROCEDURES

-STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: DIKE SPILL, REMOVE WITH ABSORBENT TO LANDFILL IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS, DOUSE ALL FLAMES AND EVACUATE AREA

WASTE DISPOSAL METHOD: STANDARD FOR SOLVENT DRUMS. SEND TO LICENSED RECLAIMER, OR APPROVED LANDFILL IN COMPLIANCE WITH APPLICABLE REGULATIONS

SECTION VIII. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION [SPECIFY TYPE]: NOT NEEDED WITH ADEQUATE VENTILATION. HIGH VAPOR OR MIST CONCENTRATIONS MAY REQUIRE A NIOSH APPROVED ORGANIC VAPOR RESPIRATOR.

VENTILATION: ADEQUATE VENTILATION NEEDED

PROTECTIVE GLOVES: NOT NEEDED

EYE PROTECTION: SAFETY GLASSES WITHOUT SIDE SHIELDS ARE SUGGESTED

OTHER PROTECTIVE EQUIPMENT: AS REQUIRED BY YOUR COMPANY

SECTION IX. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: KEEP CONTAINER CLOSED WHEN NOT IN USE. DO NOT EAT, DRINK, OR SMOKE IN WORK AREA.

OTHER PRECAUTIONS: STORE INDOORS IN COOL DRY LOCATION. VAPORS ARE HEAVIER THAN AIR, AND MAY COLLECT IN LOW AREAS; DO NOT ENTER WITHOUT ADEQUATE BREATHING APPARATUS AND AN OBSERVER FOR ASSISTANCE.

SECTION X. EFFECTS OF PROLONGED EXPOSURE

NONE KNOWN

SECTION XI. CARCINOGENIC HAZARD

NO COMPONENT IN THIS PRODUCT HAS BEEN LISTED AS A CARCINOGEN BY IARU, N.T.P., OSHA OR ACGIH.

SECTION XII. SARA TITLE III REPORTING

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS REQUIRED TO BE REPORTED UNDER SARA TITLE III, SECTION 313: NONE

THIS DATA IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EXPRESS OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEST OF THE INTENDED USE, AND DETERMINE WHETHER THEY ARE APPROPRIATE. THE INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET IS BELIEVED TO BE CORRECT AS OF THIS DATE. THE REGULATIONS PROMULGATED BY OSHA FOR HAZARD COMMUNICATION, 29 CFR 1910.1200, AS WELL AS SEVERAL STATE AND LOCAL LAWS AND REGULATIONS, HAVE BEEN CONSULTED IN PREPARING THIS M.S.D.S.